

Low VOC Plastic Magic P/N: 1051-1,1051-4

Adhesion Promoter

Low VOC Plastic Magic works like magic to improve adhesion and help prevent paint peeling on new unfinished plastic parts and previously painted surfaces. Low VOC Plastic Magic is a clear adhesion promoter that modifies the surface properties of “difficult” polyolefin plastics like polypropylene, TPO and TEO, making the surface receptive to adhesion by paints and fillers.

Benefits:

- Lower VOCs!
- Prevents paint peeling on new unfinished plastic parts and previously painted surfaces.
- No need to identify plastic. Low VOC Plastic Magic works on all plastics.
- Easy to use. Just spray on and allow to flash off.
- Plastic Magic can be top coated with any type of paint system or body filler.
- Made in USA!

Application:

- Clean first with 1020 Scuff Soap and water to remove water soluble contaminants.
- Clean with 1001-4 EcoPrep Plastic Cleaner or 1000 Super Prep Plastic Cleaner to remove mold release agents and other contaminants.
- Apply a medium wet coat of Low VOC Plastic Magic and allow to dry 10 minutes before topcoating. Topcoat within 1 hour.



VOC:
439 g/L
3.7 lb/gal

Dry Time

	Dry Time
Room Temp.	10 min.

Part Numbers

Size	Part Number
Quart	1051-4
Gallon	1051-1

Specifications

Size	Shipping Weight	Dimensions
Quart	2.1 lbs.	7.5" h x 4.6" w x 2.4" d
Gallon	7.4 lbs	10.2" h x 6.6" w x 4.2" d

Application

	Product	Recommended
Spray Temperature	50°F - 95°F	72°F
Gun Nozzle Size	.8 - 1.8 mm	1.2 mm



Customer Support:
Toll Free: 800-633-3047
Phone: 256-638-4103
www.polyvance.com